

BEST AVAILABLE COPY

WHAT IS CLAIMED IS:

1. An ink-jet printing apparatus for printing a visible image on a print medium by discharging ink from a plurality of ink ejection print elements, comprising:
- 5 means for storing a first table indicating a correspondence between a plurality of inks and gray scale values of print pixels;
- means for storing a second table indicating combinations of density distribution patterns of print
- 10 pixels and the ink ejection print elements in correspondence with the gray scale values;
- designation means for designating a region consisting of a predetermined number of neighboring pixels from pixels that forms an input image;
- 15 selection means for selecting the pixel density distribution pattern for the designated region; and
- control means for controlling ink ejection/non-ejection of ink from the plurality of ink ejection print elements by looking up the first and
- 20 second tables in accordance with the pixel density distribution pattern and a gray scale value thereof.
2. The apparatus according to claim 1, wherein said control means looks up the first and second tables on the basis of a value near a value obtained by dividing
- 25 a sum total of gray scale values of pixels which forms the region by the predetermined number of pixels.

BEST AVAILABLE COPY

Sub B1 Ant
3. The apparatus according to claim 1, wherein said selection means selects the pixel density distribution pattern on the basis of a difference between a value of a pixel of interest of the pixels that form the region,
5 and an average value of gray scale values of all pixels which form the region.

Sub A6
10 4. The apparatus according to claim 1, wherein a plurality of combinations of density distribution patterns of the print pixel and ink ejection print elements are prepared for a single gray scale value, and said control means sequentially or randomly selects these combinations.

15 5. The apparatus according to claim 1, wherein said control means adopts an ink-jet printing method of discharging double ink droplets onto at least a single unit pixel, and prints the visible image by discharging one or plurality of ink droplets onto the unit pixel.

20 6. The apparatus according to claim 1, wherein said control means adopts an ink-jet printing method of discharging ink droplets having at least two different dot sizes, and prints the visible image by discharging one or plurality of ink droplets onto a unit pixel.

25 7. The apparatus according to claim 1, wherein said control means adopts an ink-jet printing method of discharging at least two multi-density ink droplets for the same hue, and prints the visible image by

BEST AVAILABLE COPY

discharging one or plurality of ink droplets onto a unit pixel.

8. The apparatus according to claim 1, wherein the plurality of ink ejection print elements are integrated and line up, and express a halftone image by controlling a plurality of ink dots to land on substantially a single print pixel on a print medium when they are scanned a plurality of number of times in a direction different from the line-up direction while being moved relative to a print medium by a predetermined width in a direction different from the scan direction.

9. An ink-jet printing method for printing a visible image on a print medium by discharging ink from a plurality of ink ejection print elements, comprising:

the designation step of designating a region consisting of a predetermined number of neighboring pixels from pixels that forms an input image;

the selection step of selecting a pixel density distribution pattern for the designated region; and

the control step of controlling ink ejection/non-ejection of ink from the plurality of ink ejection print elements by looking up a first table indicating a correspondence between a plurality of inks and gray scale values of print pixels and a second table indicating combinations of density distribution patterns of print pixels and the ink ejection print

BEST AVAILABLE COPY

elements in correspondence with the gray scale values in accordance with the pixel density distribution pattern and a gray scale value thereof.

Sub 96
10. The method according to claim 9, wherein the control step includes the step of looking up the first and second tables on the basis of a value near a value obtained by dividing a sum total of gray scale values of pixels which forms the region by the predetermined number of pixels.

Sub 96
11. The method according to claim 9, wherein the selection step includes the step of selecting the pixel density distribution pattern on the basis of a difference between a value of a pixel of interest of the pixels that form the region, and an average value of gray scale values of all pixels which form the region.

Sub 97
12. The method according to claim 9, wherein a plurality of combinations of density distribution patterns of the print pixel and ink ejection print elements are prepared for a single gray scale value, and the control step includes the step of sequentially or randomly selecting these combinations.

13. A computer readable memory that stores a program code of an ink-jet print process for printing a visible image on a print medium by discharging ink from a plurality of ink ejection print elements, comprising:

BEST AVAILABLE COPY

a program code of the designation step of designating a region consisting of a predetermined number of neighboring pixels from pixels that forms an input image;

5 a program code of the selection step of selecting a pixel density distribution pattern for the designated region; and

a program code of the control step of controlling ink ejection/non-ejection of ink from the plurality of
10 ink ejection print elements by looking up a first table indicating a correspondence between a plurality of inks and gray scale values of print pixels and a second table indicating combinations of density distribution patterns of print pixels and the ink ejection print
15 elements in correspondence with the gray scale values in accordance with the pixel density distribution pattern and a gray scale value thereof.

Sub
a7

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100

add a8